

# SULLAIR MDT-22 & MDT-30 DEMOLITION TOOLS

## Two Bolt Backhead

This unique design reduces handle breakage. The common problem of a threaded handle-to-barrel connection coming loose and damaging the handle and internal parts is therefore eliminated.

## D-Handle

The strong "D" configuration is large enough to provide a comfortable, sure grip even for a gloved hand.

## Minimal Lubrication Required

With its unique design and materials, normal oil carry-over from the compressor, combined with moisture in the air, will usually provide sufficient lubrication under normal operating conditions.

## Smoother Operation

The Sullair demolition tool's unique design results in greater operator comfort.

## Stroke Length

The piston has been sized relative to the length of the stroke to provide an improved weight/power ratio.

## Air Inlet Option

Two air inlet bushings are furnished: 3/8" NPT and 7/8"-24, internal thread. The bushings provide for versatile hose connections while protecting the handle inlet threads.

## Exhaust Deflector

Directs exhaust air away from the operator and provides a comfortable grip. It also greatly decreases the sound level of the tool.



MDT-22 uses standard 7/8" X 3 1/4" shanks.

## DEMOLITION TOOL SPECIFICATIONS

	MDT-22	MDT-30
<b>Net Weight</b>	24.7 lbs.	33 lbs.
<b>Length</b>	20"	24.5"
<b>Shipping Weight</b>	26 lbs.	35.6 lbs.
<b>Bore and Stroke</b>	1.5 X 4.5"	1.4 X 7.4"
<b>Blows per Minute</b>	1450	1000
<b>Air Consumption</b>	33.4	37.1
<b>Air Inlet Diameter</b>	3/8" NPT or 7/8"-24	3/8" NPT or 7/8"-24
<b>Shank</b>	7/8 hx X 3 1/4	11 X Jumbo
<b>Retainer</b>	Latch	Screw-on


## MDT-22

The MDT-22 has quick change latch retainer and utilizes standard 7/8" X 3 1/4" hex steel. 2 year warranty



## MDT-30

The MDT-30 has reliable screw-on retainer (no springs) and utilizes standard 11 x Jumbo rivet buster steel, sleeves and bumpers. 1 year warranty, excluding wear items, sleeves and bumpers.



MDT-30 uses 11X Jumbo steel.