

SULLAIR M SERIES CONCRETE VIBRATORS

- CHROME CYLINDERS, EASY TO CLEAN.
- ADJUSTABLE THROTTLE FOR OPTIMUM PERFORMANCE.
- ONLY ONE MOVING PART.
- MINIMUM ON SITE LUBRICATION.
- STANDARD HOSE LENGTH 10'.

Applications

Concrete Vibrators are designed for low slump pours of concrete footings, slabs and walls. The correct diameter tool depends on wall thickness or concrete depth.

SULLAIR CONCRETE VIBRATOR SPECIFICATIONS

	MCV-300	MCV-400	MCV-580	MCV-780
Diameter	1 $\frac{3}{8}$ "	1 $\frac{1}{8}$ "	2 $\frac{1}{4}$ "	3 $\frac{1}{8}$ "
Weight	5.3 lbs.	9 lbs.	18 lbs.	33 lbs.
Air Required	16 cfm @ 90 psi	17 cfm @ 90 psi	35 cfm @ 90 psi	51 cfm @ 90 psi
Hertz	18000	17000	16000	13800



SULLAIR CORPORATION, 3700 East Michigan Blvd., Michigan City, IN 46360 Telephone: 1-800-SULLAIR or 1-219-879-5451 Fax: 1-219-874-1504